

**BADU<sup>®</sup>Jet** *perla*

**BADU<sup>®</sup>Jet** *stella*

**BADU<sup>®</sup>Jet** *riva*



# NEW GENERATION OF BADU JET



Top product designers have given the next generation of renowned BADU Jet overhang counter swim units an attractive and sporty look, while material properties and operation are now both at the technological cutting edge. We present:

- **BADU® Jet *perla*** as successor to the BADU Jet Impulse Version 2
- **BADU® Jet *stella*** as successor to the BADU Jet Action Version 2
- **BADU® Jet *riva*** as successor to the BADU Jet Swing Version 2

The power requirements previously provided by the outgoing model will be covered by the three new models of the BADU Jet generation.

Whether as an attractive wave and air bubble bath for a soothing underwater massage, or as a sporting endless no-lap swimming challenge, our counter swim units create exciting new experiences in your pool!

	<b>BADU® Jet <i>perla</i></b> (Badu Jet Impulse)	<b>BADU® Jet <i>riva</i></b> (Badu Jet Swing)	<b>BADU® Jet <i>stella</i></b> (Badu Jet Action)
Jet-pump	21-81/31 G	21-81/32 G 21-81/32 RG	21-81/33 G
Flow rate of pump (m <sup>3</sup> /h)	40/40	58/54	75
Voltage (V)	3 N- 400 1- 230 V	3 N- 400 1- 230 V	3 N- 400
Power input P <sub>1</sub> (kW)	2,10/2,30	3,30/2,90	3,80
Power output P <sub>2</sub> (kW)	1,60/1,60	2,60/2,20	3,00
Flow pressure at nozzle (bar)	0,90/0,90	1,10/1,00	1,00
Flow velocity in centre 2 m from the nozzle (m/s)	1,10/1,10	1,20/1,15	1,40
Massage pressure max. (bar)	1,20/1,20	1/1	2
Number of nozzle diameter 40 mm	1/1	1/1	2
Omnidirectional swivel nozzle (degrees)	60	60/60	60
Approx weight (kg) *with telescopic	3- /1- 36/41 / 39 <sup>*)</sup> /44 <sup>*)</sup>	3- /1- 52/52 / 55 <sup>*)</sup> /55 <sup>*)</sup>	3- 54/60

The sporty and elegant design of the new overhang counter swim units BADU Jet Perla, BADU Jet Riva and BADU Jet Stella affords a stylish and eye-catching detail to every pool.

Made of high-grade plastic, the housing offers excellent resistance and robust properties. A special coating creates an exceptionally bright white glossy finish that increases scratch resistance and provides outstanding UV stability and chemical resistance. From a functional perspective, the smooth, dirt-repellant surface also ensures that the new unit will stay looking at its best for years come.

Our three new overhang counter swim units are suitable for all in-ground pools. For above ground pools, a telescopic support offers the necessary stability. A hand-priming pump is included and ensures easy handling for one-off deaeration and filling of the unit the spring or during commissioning.

The nozzles of the three new overhang systems can be pivoted around 60 degrees in all directions. The nozzles also control the flow volume. By adjusting the power switch, sparkling air bubbles can be introduced into the flow. A second switch activates the atmospheric LED lighting that is built-in to every system. Customers have a choice between either white or multi-colored lighting. To complete the package, massage hoses and attachments are available as optional accessories, as in our cunter range.

Dimensioned draw (in mm)  
Dimensions valid for versions with 1 and 2 nozzles.

